

Pinger HR140series Handrails

Suggested Specifications

PART 1 – GENERAL

1.01 SUMMARY

- A. HR140 series Handrail system for pedestrian safety and wall protection

1.02 SECTION INCLUDES

- A. HR140 Handrail System

1.03 QUALITY ASSURANCE

- A. Performance Requirements: Provide handrail systems that conform to the following requirements of regulatory agencies and the quality control of Wall Protection Systems, Pinger.
 - 1. Fire Performance Characteristics:
Provide handrails conforming with EN13501 - 1 Class B fire rating. FLAME SPREAD AND SMOKE:ASTM E84-17 Class A, The smoke concentration is qualified, non-toxic, and there is no dripping when burning.
 - 2. Fungal and Bacterial Resistance:
The resin material is rich in silver ions,inhibiting the fungal growth on the surface of wall panel,such as the growth of pathogenic organisms such as Escherichia coli,staphylococcus aureus .Antibacterial proof ASTM E2180
 - 3. Mould Proof:
ASTM G21-15,Excellent, moisture-proof and mildew-proof, inhibit aspergillus brasiliensis , penicillium rope,short-stemmed sprouted mould,bulbar hairy shell and trichoderma viride.
 - 4. Horizontal burning:
As tested in accordance with the procedures specified in UL94HB, Standard Test Method for Rate of Burning and/or Extent and Time of Burning of Self-Supporting Plastics in a Horizontal Position.
 - 5. Impact Strength:
Provide rigid Vinyl profile materials that have an Impact Strength of 1kg as tested in accordance with the procedures specified in ASTM D256- 10EL,GB8624 -2012, Impact Resistance of Plastics.
 - 6. Environmental friendly:
No any toxic gas, formaldehyde is qualified.You can check in immediately, and there is no need to absorb formaldehyde TVOC:ISO 16000-3-6-9 AND SGS:CA CDPH 01350 -VOC
 - 7. Does not stain:
Strong, water proof,easy to clean the surface,Anti-pollution, not easy to dye , Staining test:EN423:2001.
 - 8. ISO Certified:
Provide ISO9001/ 14001/45001 Certified material. Profiles shall meet the requirements of ISO9001/ 14001/45001 Certification Standards for Low-Emitting Products and ISO9001/ 14001/45001 Product Emission Standard.

Pinger HR140 series Handrails

Suggested Specifications

9. Chemical and CORROSION Resistance:

Tested according to ASTM D 543- 14/ASTM D2240- 15/ASTM D638- 14,Excellent, small coefficient of thermal expansion and cold contraction, and almost no change in temperature size.,Antibacterial and bacteriostatic, effectively resisting most acids, alkalis, salts, alcohols,Corrosion of iodine, vegetable oil, liquor, etc.

10. No heavy metals:

Does not contain lead, cadmium and other toxic and harmful heavy metals,Heavy Metal Test:CA65

11. Durable and easy to install:

Durable,Wear-resistant, not easy to scratch the surface, dirt, dust ,Not easy to attach, not fouling, simple maintenance.Convenient construction, construction, no noise.

1.04 SUBMITTALS

- A. Product Data: Manufacturer's printed product data for each type of handrail specified.
- B. Detail Drawings: Mounting details with the appropriate fasteners for specific project substrates.
- C. Samples: Verification samples of handrail,in full size profiles of each type and color indicated.
- D. Manufacturer's Installation Instruction: Printed installation instructions for each handrail.

1.05 DELIVERY, STORAGE AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite
- B. Inspect materials at delivery to assure that specified products have been received.
- C. Store in original packaging in a climate controlled location away from direct sunlight.

1.06 PROJECT CONDITIONS

- A. Environmental Requirements: Products must be installed in an interior climate controlled environment.

1.07 WARRANTY

- A. Standard Pinger Limited Lifetime Warranty against material and manufacturing defects.

PART 2 – PRODUCTS

2.01 MANUFACTURED UNITS

- A. *Handrail Profile (Dimensions, Color Option, Series Number)*

1. 38mm gripping diameter, extends 38mm from wall. Handrail shall be a solid color. - HR140 series Handrail

2.02 MATERIALS

- A. Vinyl: 2MM thick
- B. The installation connection accessories are made of Vinyl & Aluminum material.
- C. Brackets shall be made of type ABS

2.03 COMPONENTS

- A. Vinyl left end cap, right end cap, outside end cap and ABS bracket with fastener
- B. Fasteners: All mounting systems accessories appropriate for substrates indicated on the drawings shall be provided, unless installer supplied is indicated.

PART 3 – EXECUTION

3.01 EXAMINATION

- A. Examine areas and conditions in which the handrail systems will be installed.
 1. Complete all finishing operations, including painting, before beginning installation of handrail system materials.
- B. Wall surface shall be dry and free from dirt, grease and loose paint.

3.02 PREPARATION

- A. Surface Prep: Prior to installation, clean the substrate to remove dust, debris and loose particles. Ensure the substrate is sound and per project plans.
- B. Acclimate product in temperatures between 65°F and 80°F [18°-27°C] and a humidity level less than 80% 24 hours in advance of installation.
- C. The area of installation must temperature and humidity controlled for at least 48 hours after installation.

3.03 INSTALLATION

- A. General: Locate the handrail as indicated on the approved detail drawing for the appropriate substrate and in compliance with the Pinger installation instructions. Install handrail level and plumb at the height indicated on the drawings.

3.04 CLEANING

- A. At completion of the installation, clean surfaces in accordance with the Pinger clean-up and maintenance instructions.

Technical Data Sheet

- Resistant to certain bacterial & fungal growth & Mould Proof (ASTM G 21-15) .
 - Class A fire and smoke rating. (per ASTM E84-17)
 - Class B fire and smoke rating (per GB8624-2012)
 - Horizontal Burning (per UL94HB)
- Chemical And Corrosion resistant (per ASTM D 543-14/ASTM D2240-15/ASTMD638-14) .
 - Impact resistant (per ASTM D256-10el And GB/T 14153-1993) .
 - TVOC (per CA CDPH 01350-voc)
 - Color Difference (per SAEJ1545-2005)
 - Color Staining (per EN423:2001)
 - Phthalate Test (per SGS)
 - Formaldehyde (per CA CDPH 01350-voc And GB/T 18580-2017)
 - Heavy Metal Test (per CA65)

Installation Instruction

- Bolts&Screws
- Cut aluminum retainer (rubber strip) to desired length
 - Drill the holes
- Measure and transfer the handrail mounting hole locations from the bracket,elbow.
 - Cut the vinyl cover to the lengths between returns and elbows.

TECHNICAL DATA		
Certificate	Certificate standard	Result
Antibacterial	ASTME2180	>99.9% inhibis growth
Mould Proof	ASTM G21-15	0 Class non growth
Fire and smoke Rating	ASTM E84-17 Class A	Class A
Horizontal Burning	UL94HB	PASS
Crashproof	ASTM D256-10el	PASS
Chemical and Corrosion resistance	ASTM D543-14/ASTM D2240-15/ASTM D638-14	G00D
TVOC	CA CDPH 01350-voc	G00D
Color Diference	SAEJ1545-2005	G00D
Color staining	EN423: 2001	G00D
Phthalate Test	SGS	PASS
Fomaldehyde	CA CDPH 01350-voc GB/T 18580-2017	PASS
Heavy metal Test[Lead& Cadmium	CA65	PASS
Application		
Hospital hotel airport, High-end office building High-end Vila, kKindergarten, School , Sport Hal, Factory, .Plane, High-speed Train, Loose pulley.public place and so on.		

CARE INSTRUCTIONS

Cleaning And Maintenance Requirements		
Visitor folw rate	cleaning and maintenance	Stain processing
Privte room	one time in one year	Require time
Public place or corridor	two or three times in one year	Require time
Main channel or main entry door	one time lin one month	Require time

Remark:

- 1、 Daily cleaning and maintenance ,it can be used to clean the dust layer with a clean cloth
- 2、 If there are a few stains: footprints,tea marks,etc,use a clean cloth to wipe
- 3、 If the stain is not timely treatment,stay too long,use a clean cloth and neutral cleaner to wipe.
- 4、 Use dishcloth to add warm warm water or cleaner to wipe, need to use clean dry dishcloth to wipe Water mark.

Cleaning tool selection:

(1)clothes: clean clothes or scouring pad

(2)cleaner: nataural cleaner

Special remind:

- Use dishcloth to add warm water or cleaner to wipe. Need to use clean dry dishcloth to wipe Water mark.